



| Pin Out | |
|---------|--------|
| 1 | UR |
| 2 | UL |
| 3 | SHIELD |
| 4 | LL |
| 5 | LR |

- NOTES:
1. GLASS OPTICAL CHARACTERISTIC IS CLEAR TYPE
 2. TOPSHEET GLASS THICKNESS 2.8mm
 3. FLEXTAIL DO NOT BEND TO LESS THAN 3.175mm RADIUS
 4. TAIL ACCEPTS 2.54mm PITCH
 5. INSULATION TAPE : POLYESTER TAPE , TOTAL THICKNESS 0.063mm , BLACK
 6. REINFORCE TAPE : POLYESTER TAPE , TOTAL THICKNESS 0.1mm , BLACK
 7. ACETATE ADHESION TAPE : TOTAL THICKNESS 0.25mm , BLACK
 8. 5 PIN AMP CONNECTOR, LATCH STYLE HOUSING P/N:487526-4 OR EQUIVALENT

| | | | |
|------------------------|------------|--------------|----------|
| THIRD ANGLE PROJECTION | | Dimensions | m/m |
| Drawn by | Kawa Huang | Scale | FREE |
| Checked by | | Release Date | 10,13'04 |

eTurboTouch

Drawing Number SS-151E75P5L5PS1